

Data Evaluation for ^{19}F , ^{35}Cl , ^{37}Cl , ^{241}Pu , ^{238}U , and Gd Isotopes

Luiz Leal, Herve Derrien, Royce Sayer, Nancy Larson

Nuclear Data Group

Nuclear Science and Technology Division

Oak Ridge National Laboratory

CSEWG

Brookhaven National Laboratory

November 4-6, 2003

^{35}Cl and ^{37}Cl Resonance Evaluation

Nuclear Science and Technology Division




Features:

- Total cross section, capture cross section, and (n,p) cross section data measurements were used in the evaluation.
- Evaluation performed up to 1.2 MeV.
- 380 s- and p-wave. 244 for ^{35}Cl and 136 for ^{37}Cl .
- SAMMY: Reich-Moore formalism was used.
- Charge particle (n,p) exit channel not accommodated in existing ENDF format: **Format modification proposed !!**



Chlorine Cross Section

Nuclear Science and Technology Division




Chlorine Cross Section

Nuclear Science and Technology Division




Comparison with ENDF

Nuclear Science and Technology Division



Comparison with ENDF

Nuclear Science and Technology Division



^{19}F Evaluation


Nuclear Science and Technology Division




Experimental Data

- **Three Transmission Data Measurements of Larson *et al.* made at ORELA 80 meters flight path with sample thicknesses 0.13093 at/b, 0.016886 at/b, and 0.024184 at/b, respectively in the energy range 5 eV to 20 MeV.**
- **One Capture measurement done at ORELA 40 meters flight path performed by Guber *et al.* up to 700 KeV;**
- **Inelastic Cross Section Measurements Performed by Broder *et al.* at Obninsk up to 1 MeV. (Format modification proposed)**


Transmission




Total and Capture Cross Sections




Inelastic Cross Sections



Comparison with ENDF evaluation



Comparison with ENDF evaluation



Direct Capture Cross Section for ^{19}F

Nuclear Science and Technology Division



SAMMY allows the fit of the direct capture component of the cross section as suggested by Kerman and Dietrich

Total Capture = resonance component + direct capture component

$$\sigma_{\gamma}^{tot} = \sigma_{\gamma}^{res}(E_n, \Gamma_n, \Gamma_{\gamma}) + C \times \sigma_{\gamma}^{direct}$$

Example: ^{19}F



- Model calculations by Goran Arbanas, ORNL
- Analysis by Luiz Leal, ORNL
 - Multiplier initially at 1.0, fitted to 0.547


^{19}F (continued)

+ = data

Nuclear Science and Technology Division



Capture cross section (barn)



dash = R-matrix contribution

long dash = direct component

solid line = sum of the two components

^{241}Pu Evaluation

Nuclear Science and Technology Division



Motivation

- **Investigation of the French Post-Irradiation Experiments (PIE) on PWR Indicates Significant Underestimation of the ^{241}Pu Capture Cross Section;**
- **Underestimation in the build-up prediction of ^{243}Am , ^{244}Cm , and ^{245}Cm ;**

The Evaluation was performed in the energy range thermal to 20 eV;

Paper submitted to Nuclear Science and Engineering.

^{241}Pu Evaluation

Nuclear Science and Technology Division



Experimental Data Bank

- **Weston fission and capture data (1976);**
- **Wagemans fission data (1991);**
- **Young and Smith total cross section (1968);**

All data normalized in the energy range 0.01 eV to 1 eV according to Wagemans fission and Young total cross section.

Results

Nuclear Science and Technology Division



E_r 0.26 eV	ϵ_c meV	ϵ_n meV	ϵ_{f1} meV	ϵ_{f2} meV
1988	32.555	0.04371	-78.04	-0.481
1993	33.350	0.04252	-50.42	25.36
This Work	34.630	0.04367	-42.71	32.06

Results

Nuclear Science and Technology Division



E_r 0.0253 eV	Standard (barns)	Present work (barns)
Fission	1012.68 ± 6.58	1012.20
Capture	361.29 ± 4.95	363.0
Scattering	12.17 ± 2.62	11.3
Total	1386.14 ± 8.64	1386.5

Results

(C/E-1 in % using JEF2.2, JENDL3.2, and ORNL evaluation)

Nuclear Science and Technology Division



BU (Gwd/t)	26.9	38.4	50.3	59.8
Pu241/U238(JEF2.2)	-6.3 ± 2.3	-5.0 ± 1.8	-3.8 ± 1.6	-3.1 ± 1.6
Pu242/U238(JEF2.2)	-10.5 ± 4.0	-9.7 ± 3.4	-8.8 ± 3.1	-8.6 ± 2.8
Am243/U238(JEF2.2)	-18.0 ± 6.2	-11.6 ± 5.2		-8.8 ± 4.4
Pu241/U238(JENDL3.2)	-5.4 ± 2.3	-3.8 ± 1.8	-2.5 ± 1.6	-1.6 ± 1.6
Pu242/U238(JENDL3.2)	-9.0 ± 4.0	-7.9 ± 3.4	-6.8 ± 3.1	-6.4 ± 2.8
Am243/U238(JENDL3.2)	-16.6 ± 6.2	-9.9 ± 5.2		-6.8 ± 4.4
Pu241/U238(ORNL)	-5.9 ± 2.3	-4.4 ± 1.8	-3.1 ± 1.6	-2.4 ± 1.6
Pu242/U238(ORNL)	-5.2 ± 4.0	-4.3 ± 3.4	-3.2 ± 3.1	-2.9 ± 2.8
Am243/U238(ORNL)	-12.8 ± 6.2	-6.5 ± 5.2		-3.7 ± 4.4

²³⁸U Evaluation

Nuclear Science and Technology Division



- Resonance Analysis done in the Energy Region From 10^{-5} eV to 20 keV;
- Two Sets of Resonance Parameters: 0 to 10 keV and 10 keV to 20 keV;
- ENDF/B-VI Resonance Parameters below 10 keV were used for Starting Values;
- Extension of the ENDF/B-VI Resolved Resonance Region from 10 keV up to 20 keV;
- Evaluation done with the Reich-Moore formalism in the code SAMMY;
- High Resolution Data of Harvey et al. and Capture Cross Section Data of DeSaussure were used.
- Accurate Self-Shielding and Multiple Scattering Correction for Capture Data were done with an Improved Version of SAMMY;

Energy Range 1 keV to 10 keV

Nuclear Science and Technology Division



- Starting with the ENDF/B-VI Resonance Parameters (Moxon-Sowerby Evaluation);
- Experimental Data Used:
 - Olsen transmission data (1977) (four thicknesses)
 - Harvey Transmission Data: Three thicknesses: 0.1748, 0.0396, and 0.0125 atoms/b; Data measured at ORELA on the 200 m flight path
 - Capture Data of DeSaussure measured at ORELA on the 40 m flight path

Results for the evaluation energy region 1 keV to 10 keV

Nuclear Science and Technology Division



- Modification of the external resonance parameters for accurate description of the transmission data between resonances. The average scattering cross section increases by 2.8 %;
- Scattering Radius of 9.450 fm in agreement with the Olsen ORNL Evaluation;
- Better description of the Capture data. The average capture cross section increases by 3.8 % in the energy range 1 keV to 10 keV;

Average ^{238}U Cross Sections (1 keV to 10 keV)

Nuclear Science and Technology Division



Energy Range (keV)	Capture (b)		Elastic (b)	
	ENDF/B-VI	ORNL	ENDF/B-VI	ORNL
1 – 2	1.87	1.94	21.68	22.25
2 – 3	1.36	1.41	21.57	22.12
3 – 4	1.15	1.20	19.82	20.36
4 – 5	0.88	0.89	14.79	15.03
5 – 6	0.90	0.90	14.20	14.38
6 – 7	0.87	0.88	16.66	16.37
7 – 8	0.68	0.74	13.79	14.07
8 – 9	0.63	0.65	15.03	15.71
9 – 10	0.65	0.71	13.07	13.89
1 - 10	1.00	1.04	16.73	17.12

Energy Range 10 keV to 20 keV

Nuclear Science and Technology Division



- **No prior values of the resonance parameters existed;**
- **Experimental Data Used:**
 - **Harvey Transmission Data: Three thicknesses: 0.1748, 0.0396, and 0.0125 atoms/b; Data measured at ORELA on the 200 m flight path**
 - **Capture Data of DeSaussure measured at ORELA on the 40 m flight path**

Results for the evaluation energy region 10 keV to 20 keV


Nuclear Science and Technology Division



- 457 s-wave resonances and 1228 p-wave resonances obtained with SAMMY analysis of Harvey transmission data and DeSaussure Capture cross section data
- The average capture cross section agrees with the ENDF/B-VI evaluation;
- The average elastic cross section is larger than the ENDF/B-VI evaluation by 3.1 %;


Effective Total Cross Section from the Transmission Data (upper curve x 100, middle curve x 10)

Nuclear Science and Technology Division



Effective Capture Cross Sections

Nuclear Science and Technology Division



Average ^{238}U Cross Sections (10 keV to 20 keV)

Nuclear Science and Technology Division



Energy Range (keV)	Capture (b)		Elastic (b)	
	ENDF/B-VI	ORNL	ENDF/B-VI	ORNL
10 – 11	0.71	0.68	14.67	14.72
11 – 12	0.68	0.65	14.53	13.91
12 – 13	0.66	0.65	14.40	15.32
13 – 14	0.64	0.72	14.29	14.56
14 – 15	0.62	0.62	14.18	15.54
15 – 16	0.60	0.58	14.09	14.60
16 – 17	0.58	0.58	14.01	13.79
17 – 18	0.57	0.58	13.93	16.25
18 – 19	0.55	0.53	13.86	14.57
19 - 20	0.54	0.52	13.79	12.91
10 - 20	0.615	0.611	14.17	14.62

Statistical Properties of Resonance Parameters in the Energy Range 10 keV to 20 keV


Nuclear Science and Technology Division



- Number of Resonances used to fit the data are 457 s-wave and 1228 p-wave;
- Below 10 keV ENDF/B evaluation uses 473 s-wave and 1228 p-wave;
- Spin Assignment:
 - Large resonances are assigned s-wave from their shape;
 - Small resonances are distributed among 3 families: s-wave, p-wave $p_{1/2}$ and $p_{3/2}$ following the $2J+1$ spin dependence of the population;


Distribution of s-wave Level Spacings

Nuclear Science and Technology Division




Distribution of p-wave Level Spacings

Nuclear Science and Technology Division




Porter-Thomas Distribution of s-wave neutron widths

Nuclear Science and Technology Division



Porter-Thomas Distribution of p-wave neutron widths

Nuclear Science and Technology Division



Neutron Strength Functions

Nuclear Science and Technology Division



ORNL Results 10 keV to 20 keV	ENDF/B-VI From Thermal to 10 keV
S_0 $(1.120 \pm 0.074) 10^{-4}$	S_0 $(0.947 \pm 0.07) 10^{-4}$
S_1 $(1.693 \pm 0.068) 10^{-4}$	S_1 $(1.577 \pm 0.06) 10^{-4}$

Benchmark results using ^{238}U ORNL Evaluation

Nuclear Science and Technology Division



Thermal benchmark (Leu-Comp-Therm Series)

Thermal Benchmark Experiments Performed at the Tank-type Critical Assembly TCA facility (JAERI, Japan) from 1963 to 1975

TCA

Tank-type Critical Assembly, light water moderated and fueled with low enriched uranium (2.6 wt % of UO_2) with a size of 1.8m in diameter and 2m long, controlled by reactor core water level. The water to fuel volume ratio ranges from 1.5 to 3.0

Benchmark Results

Nuclear Science and Technology Division



- Calculations done with MCNP4C code
- Base library used was the ENDF/B-VI release Five
- Calculations done with 1000 histories per cycle with 3000 cycles
- Two sets of results:
 - a) Calculations with MCNP library based on ENDF/B-VI.5
 - b) Calculations with MCNP library based on ENDF/B-VI.5 replacing ^{238}U evaluation with ORNL evaluation

Benchmark Results

Nuclear Science and Technology Division



Case	ENDF/B-VI.5	ENDF/B-VI.5 with ^{238}U ORNL Evaluation
LCT-01	0.99276 ± 0.00043	0.99506 ± 0.00043
LCT-02	0.99359 ± 0.00042	0.99429 ± 0.00043
LCT-03	0.99245 ± 0.00044	0.99568 ± 0.00042
LCT-04	0.99376 ± 0.00042	0.99534 ± 0.00041
LCT-05	0.99383 ± 0.00043	0.99471 ± 0.00042
LCT-06	0.99345 ± 0.00043	0.99654 ± 0.00042
LCT-07	0.99400 ± 0.00042	0.99604 ± 0.00042
LCT-08	0.99358 ± 0.00043	0.99610 ± 0.00043
LCT-09	0.99429 ± 0.00042	0.99582 ± 0.00041
LCT-10	0.99502 ± 0.00042	0.99767 ± 0.00041
LCT-11	0.99535 ± 0.00041	0.99704 ± 0.00041
LCT-12	0.99472 ± 0.00041	0.99619 ± 0.00042
LCT-13	0.99420 ± 0.00042	0.99557 ± 0.00042

Benchmark Results

Nuclear Science and Technology Division



Case	ENDF/B-VI.5	ENDF/B-VI.5 with ^{238}U ORNL Evaluation
Average	0.99392 \pm 0.00042	0.99585 \pm 0.00042
An improvement of 193 pcm On average !!		

Gd Evaluation

^{152}Gd , ^{154}Gd , ^{155}Gd , ^{156}Gd , ^{157}Gd , ^{158}Gd , and ^{160}Gd

Nuclear Science and Technology Division



- **Resolved and Unresolved Resonance Evaluations Revised**
 - **MLBW resonance parameters converted to RM parameters;**
 - **Unresolved resonance evaluation done with SAMMY: Average SLBW parameters obtained.**
 - **SAMMY used to reevaluate the RM parameters.**
- **Resolved and Unresolved Resonance Covariance Evaluation done with SAMMY**
 - **Uncertainty in the Resonance Parameters reported on “Mughabghab’s Book” used as input;**
 - **“Typical” data uncertainty on “data” were used. Example: ORELA resolution function, TOF uncertainties, channel widths, jitters, etc.**
- **Use SAMMY Retroactive Scheme to Generate Covariance Data.**